



APPLICATIONS

Eni Rubus TF 000 is a high performance aluminium complex "food grade" grease formulated with pharmaceutical white oil, with PTFE and antiwear, antirust, antioxidant additives.

Eni Rubus TF 000 has a wide range of applications in food, pharmaceutical and cosmetic industries, particularly recommended for the lubrication of bearings, joints, gaskets, gears, gearboxes and chains where this consistency is requested.

Particularly suitable for centralized lubrication systems.

Eni Rubus TF 000 is formulated exclusively with additives listed in the FDA Group 21 CFR 178.3570 and it is free of genetically modified materials, main allergens substances like nut oil, soya oil, dairy industry derivatives and animal derived materials.

CUSTOMER ADVANTAGES

- Meets the requirements of the HACCP (Hazard Analysis and Critical Control Point) System thanks to NSF H1 (incidental contact with food) registration;
- Outstanding sliding properties;
- Good pumpability at low temperature;
- Good resistance to loads, shocks and vibrations;
- Good resistance to water washout;
- Very good protection of the machinery against rust and corrosion;
- Compatible with the elastomers normally used in food machinery lubrication systems.

SPECIFICATIONS - APPROVALS

- ISO 12924 L-XABDA 000
- DIN 51826 GPF 000K -10
- Kosher
- Halal
- NSF H1 - n° 151349





CHARACTERISTICS

Properties	Method	Unit	Typical
Consistency (NLGI grade)	-	-	000
Thickener type	-	-	aluminium complex
Base oil type	-	-	pharmaceutical white oil
Base Oil Viscosity at 40°C	ASTM D 445	mm ² /s	180
Solid lubricant	-	-	PTFE
Appearance	-	-	smooth
Colour	-	-	white
Dropping point	ASTM D 566	°C	200
Penetration at 60 double stroke	ASTM D 217	dmm	460
4 Balls wear	ASTM D 4172	mm	< 0.7
4 Balls weld load	ASTM D 2596	kg	200
Temperature range		°C	-15/+110

WARNINGS

- All "food grade" lubricants should be stored apart from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0° C and +40°C.

