



## APPLICATIONS

**Eni Acer EST 100** is a high performance synthetic ester-based fluid formulated to satisfy the request for environmentally friendly products that are able to minimize the environmental pollution in case of accidental leakages.

**Eni Acer EST 100** is particularly recommended for total loss lubrication of rolling bearings of stern tubes of marine vessels.

## CUSTOMER ADVANTAGES

- Protects components thanks to outstanding antiwear properties
- Effective protection from rust and corrosion
- Long term performance ensured by a very good oxidation resistance
- Compatibility with rubber types that are commonly used for seals
- Ecolabel registered

## SPECIFICATIONS & APPROVALS

- ISO 15380 HEES
- EU ECOLABEL - n° BE/27/002





## CHARACTERISTICS

Properties	Method	Unit of Measure	Min	Typical
Appearance	Visivo	-		clear
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>		926
Viscosità cinematica a 40 °C	ASTM D 445	mm <sup>2</sup> /s	90	100
Viscosity Index	ASTM D 2270	-	170	180
Pour point	ASTM D 97	°C		-36
Flash point (COC)	ASTM D 92	°C	270	290
Copper corrosion	ASTM D 130	mgKOH/g		1A
Rust test/B	ASTM D 665/B	-		pass

