



APPLICATIONS

Eni OSO 68 is a high performance antiwear hydraulic oil, specifically designed to meet the most rigorous performance requirements of a wide range of hydraulic system and component manufacturers.

It's formulated with selected base oils treated with "low zinc" technology ensuring excellent antiwear, antirust and antioxidant properties. It has an outstanding filterability in service.

Eni OSO 68 is also suitable for other duties in which lubricants of high oxidation stability and lubrication performance are required, allowing use of a single product with excellent performance characteristics.

CUSTOMER ADVANTAGES

- Prolongs oil charge life extending re-lubrication intervals thanks to very high thermo-oxidative stability
- Suitable for hydraulic systems with very thin filters (3 microns)
- Maximizes water removal system efficiency thanks to excellent demulsibility
- Protects components reducing downtime thanks to outstanding antiwear property
- Helps prevent aeration and cavitation damage in low residence time systems thanks to rapid air release
- Minimizes deposits formation contributing to system cleanliness

SPECIFICATIONS - APPROVALS

- ATOS Table P002-1/E
- Danieli Standard n. 0.000.001 - Rev.15
- Muller Weingarten DT 55 005
- BS 4231 HSD
- Fives Cincinnati P-69 level
- Denison HF-0 level
- Eaton Vickers I-286-S
- AFNOR NF E 48603 HM





- ISO 11158 HM
- DIN 51524-2 HLP
- Rexroth RD 90220-01/12.10
- Loesche

CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	APM 27	-	clear
Density at 15°C	ASTM D 4052	kg/m ³	886
Viscosity at 40°C	ASTM D 445	mm ² /s	68
Viscosity Index	ASTM D 2270	-	103
Flash point COC	ASTM D 92	°C	232
Pour point	ASTM D 5950	°C	-24
Demulsibility at 54°C	ASTM D 1401	mins	30
Foaming (sequence I)	ASTM D 892	cc/cc	0/0
Air release	DIN 51381	mins	8
Rust test/B	ASTM D 665	-	
Cleanliness class	ISO 4406	-	

