



APPLICATIONS

Eni Arnica PSX 46 is a fully synthetic high performance hydraulic fluid specifically formulated for ceramic presses; the product is particularly recommended for most modern Sacmi presses.

CUSTOMER ADVANTAGES

- Long term performances guaranteed by a very high oxidation resistance
- Prevention of filters clogging thanks to detergent and dispersant properties
- Outstanding viscosity stability due to a very high viscosity index
- Optimal protection of lubricated components from mechanical wear for their improved operative efficiency
- Performances guaranteed even in case of extremely cold temperatures
- Corrosive attack prevented by a robust antirust additivation

SPECIFICATIONS - APPROVALS

- ISO 11158 HV
- DIN 51524-3 HVLP-D





CHARACTERISTICS

| Properties | Method | Unit | Typical |
|-------------------|-------------|--------------------|---------|
| Appearance | APM 27 | - | clear |
| Density at 15°C | ASTM D 4052 | kg/m ³ | 846 |
| Viscosity at 40°C | ASTM D 445 | mm ² /s | 46 |
| Viscosity Index | ASTM D 2270 | - | 161 |
| Flash point COC | ASTM D 92 | °C | 230 |
| Pour point | ASTM D 5950 | °C | -45 |
| Rust test/B | ASTM D 665 | - | pass |

