

# Eni i-Sint professional 20W-50



## APPLICATIONS

**Eni i-Sint professional 20W-50** is a synthetic technology lubricant designed to meet the lubrication requirements of petrol or diesel fueled cars or commercial vehicles that operate according to the maintenance procedures prescribed by the manufacturers.

## CUSTOMER ADVANTAGES

- The detergent and dispersing properties resulting from the proper choice of the raw materials that are included in the product make it possible to counteract the formation of sludge, lacquers and other types of deposits, thus preserving an optimal condition of the mechanical components.
- The special formulation of **Eni i-Sint professional 20W-50** allows maximum protection of the mechanical parts of the engine against wear.
- The presence in the formulation of low volatility components and simultaneously high thermal stability reduces oil consumption caused by evaporative effects.

## SPECIFICATIONS - APPROVALS

- API SN/SM/CF



# Eni i-Sint professional 20W-50



## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	893
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	19.3
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	179
Viscosity Index	ASTM D 2270	-	122
Viscosity at -15°C	ASTM D 5293	mPa·s	9000
Flash point (COC)	ASTM D 92	°C	226
Pour point	ASTM D 97	°C	-24

