



APPLICATIONS

Eni Brake Fluid DOT 4 is a high performance hydraulic brake fluid for use in automotive disc, drum, ABS and clutch systems. The product provides good performance levels for use in passenger cars, motorcycles and commercial vehicles, both for current and previous model generation.

CUSTOMER ADVANTAGES

- **Eni Brake Fluid DOT 4** has a high boiling point that guarantee consistent and safe brake performance under severe stress condition of the braking system.
- It is compatible with rubber components, it preserves the tightness of the gaskets and it reduces leakage and loss of fluid to a minimum.
- It provides an excellent corrosion protection and it guarantees the extended life and reliability of brake system components.
- With high resistance to oxidation, **Eni Brake Fluid DOT 4** allows for long-term unaltered chemical/physical characteristics of the fluid.

SPECIFICATIONS & APPROVALS

- SAE J 1704
- FMVSS 116, DOT 4
- ISO 4925/05 (CLASS 04)





CHARACTERISTICS

Properties	Method	Unit of Measure	Typical
Density at 20°C	ASTM D 1298	kg/m ³	1040
Viscosity at -40°C	ISO 4925/05-5.1	mm ² /s	1000
Dry boiling point	ISO 4925/05-5.2	°C	260
Wet boiling point	ISO 4925/05-5.2.6	°C	163
Flash point	ISO 4925/05-5.2	°C	125

WARNINGS

- Store the brake fluid only in the original container securely closed in order to protect from moisture.

