

Eni i-Ride scooter 15W-50



APPLICATIONS

Eni i-Ride scooter 15W-50 is a high quality lubricant designed for 4-stroke scooters. Suitable for both liquid and air cooled engines, its formulation is developed to provide maximum performance even in the most severe operating conditions.

CUSTOMER ADVANTAGES

- **Eni i-Ride scooter 15W-50** ensures perfect lubrication of the engine in any operating condition.
- This product reduces the formation of deposits, ensuring maximum engine performance.
- **Eni i-Ride scooter 15W-50** keeps its features unchanged even in high temperature operating conditions.
- The product is particularly suitable for use in scooters equipped with Start & Stop systems.
- The product formulation is designed to meet any conditions of use even under particular environmental conditions.

SPECIFICATIONS - APPROVALS

- API SJ
- JASO MA, MA2



Eni i-Ride scooter 15W-50



CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	875
Viscosity at 100°C	ASTM D 445	mm ² /s	18.8
Viscosity at 40°C	ASTM D 445	mm ² /s	145
Viscosity Index	ASTM D 2270	-	145
Viscosity at -20°C	ASTM D 5293	mPa·s	6800
Flash point (COC)	ASTM D 92	°C	205
Pour point	ASTM D 97	°C	-27

